


RECORD OF SURVEY No. 32-86

IN THE UNINCORPORATED TERRITORY OF THE COUNTY OF MONO, STATE OF CALIFORNIA,
BEING ALL, OR PORTIONS OF, SECTIONS 26 THROUGH 30 AND SECTIONS 33 THROUGH 35,
TOWNSHIP 6 NORTH, RANGE 23 EAST, MOUNT DIABLO MERIDIAN

MONUMENT DESCRIPTIONS:

100200




FOUND A 36 INCH DIAMETER STONE MOUND AND DECAYED 1x2x4 INCH PIECE OF WOOD, POSITION GENERALLY AGREES WITH RECORD DIMENSIONS FROM FOUND CORNERS TO THE NORTH (100240) AND EAST (240200). ACCEPTED THE CENTER OF SAID MOUND OF STONES AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 24 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 3 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 0.5 FEET SOUTHERLY. MADE NEW BEARING TREES, BASE BLAZE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT BASE CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT1: AN 8 INCH MAHOGANY, N44°W, 30.4 FEET


BT2: A 14 INCH MAHOGANY S34°W, 10.7 FEET

100240




FOUND A 36 INCH DIAMETER STONE MOUND APPROXIMATELY ON "BANK OF SMALL LAKE" PER ORIGINAL NOTES, POSITION GENERALLY AGREES WITH RECORD DIMENSIONS FROM FOUND CORNERS TO THE NORTH (100400) AND SOUTH (100200). ACCEPTED THE CENTER OF SAID MOUND OF STONES AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 24 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 2.5 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 0.8 FEET NORTHERLY.

100400



FOUND A 2 1/2 INCH DIAMETER STAINLESS STEEL POST WITH A 3/4 INCH BRASS CAP STAMPED AS SHOWN, IN A MOUND OF STONES 3 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND PER NOTES AND PLAT OF THE BLM DEPENDENT RESURVEY, SUBDIVISION OF SECTION 23, AND SURVEY OF TRACTS 37 AND 38, T6N, R22E, MDM, ACCEPTED BY THE ACTING CHIEF CADASTRAL SURVEY-CALIFORNIA ON JANUARY 28, 2011. FOUND THE MONUMENT IN GREAT CONDITION, STRAIGHT AND SOLID, LEFT AS FOUND. ALSO FOUND A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 2.0 FEET WESTERLY.

200300



FOUND 26x12x5 INCH STONE LYING DOWNHILL TO THE SOUTHEAST OF A MOUND OF STONES. ACCEPTED THE CENTER OF SAID MOUND OF STONES AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 24 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 3.5 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. BURIED THE FOUND ORIGINAL STONE UPSIDE DOWN ALONGSIDE THE NEW MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 0.8 FEET WESTERLY. FOUND ORIGINAL BEARING TREES:

BT1: A 50 INCH YELLOW PINE, N10°W, 15.3 FEET. FOUND DEAD AND FALLEN


BT2: A 6 INCH MAHOGANY, S41°E, 37.0 FEET, FOUND DEAD BUT STANDING

ADDED, TO BT2, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT BASE CENTER RIGHT SIDE. MADE NEW BEARING TREES, BASE BLAZE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT BASE CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT3: A 12 INCH PINE, S10°E, 12.9 FEET

BT4: A 6 INCH PINE S80°E, 30.0 FEET

220300




SET A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 24 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 4 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 1.0 FOOT NORTHERLY. MADE NEW BEARING TREES, BASE BLAZE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT BASE CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT1: A 10 INCH JUNIPER, N60°W, 4.6 FEET

BT2: A 16 INCH JEFFREY PINE S15°W, 42.6 FEET

MONUMENT DESCRIPTIONS:

240200



FOUND A 1 1/4 INCH IRON PIPE AND TAG STAMPED "RCE 27104" PER R2. ALSO FOUND THE ORIGINAL 14x12x5 INCH STONE LYING NEXT TO THE PIPE. ACCEPTED SAID PIPE AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 26 INCHES IN THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. BURIED THE FOUND 1 1/4 INCH IRON PIPE AND STONE UPSIDE DOWN ALONGSIDE NEW MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN 1.0 FOOT SOUTHERLY. FOUND ORIGINAL BEARING TREES:


BT1: AN 84 INCH YELLOW PINE, S85°W, 320+/- FEET

MADE NEW BEARING TREES, BASE BLAZE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT BASE CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT2: A 7 INCH WHITE FIR, S30°E, 11.4 FEET

BT3: A 6 INCH WHITE FIR, SOUTH, 18.7 FEET

240300



FOUND A MOUND OF STONES, 3.5 FEET IN DIAMETER S81°W, 2.57 CHAINS FROM FOUND ORIGINAL BEARING TREE, RECORD WAS S65.5°W, 3.58 CHAINS. THE POSITION OF SAID MOUND GENERALLY AGREES WITH RECORD DIMENSIONS FROM THE FOUND CORNER TO THE WEST (200300). ALSO, AT RECORD FROM THE BEARING TREE THERE IS FLAT, PRISTINE DIRT, WITH NO ROCKS OR EVIDENCE OF ANY MOUND EVER HAVING EXISTED. IT IS APPARENT THAT THE RECORD DIMENSIONS FROM THE BEARING TREE MUST HAVE BEEN NOTED IN ERROR BY 1 CHAIN, AND THE ANGULAR ERROR IS NOT ABNORMAL TO WHAT HAS BEEN FOUND THROUGHOUT THIS TOWNSHIP. ACCEPTED THE CENTER OF SAID MOUND AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 22 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 3.5 FEET IN DIAMETER AND 8 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 2.0 FEET NORTHWESTERLY. FOUND ORIGINAL BEARING TREES:


BT1: A 30 INCH JUNIPER, S81°W, 169.3 FEET

ADDED, TO BT1, A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT BASE CENTER RIGHT SIDE. MADE NEW BEARING TREES, BASE BLAZE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT BASE CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT2: A 24 INCH YELLOW PINE, S10°E, 64.1 FEET


BT3: A 30 INCH YELLOW PINE, N60°E, 26.8 FEET

300100



FOUND A 1 INCH IRON PIPE AND TAG STAMPED "RCE 27104" PER R2. ENCIRCLED BY A MOUND OF STONES, 3.0 FEET IN DIAMETER AND 10 INCHES ABOVE THE GROUND. ALSO FOUND A STEEL WITNESS POST 2 FEET SOUTHWESTERLY OF THE PIPE. ACCEPTED SAID PIPE AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 24 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 3.5 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. BURIED THE FOUND 1 INCH IRON PIPE UPSIDE DOWN ALONGSIDE NEW MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 2.0 FEET NORTHWESTERLY. NO ORIGINAL OR NEW BEARING TREES IN THE VICINITY.

300120




FOUND A 1 INCH IRON PIPE AND TAG STAMPED "RCE 27104" PER R2, FLUSH, ENCIRCLED BY A MOUND OF STONES, APPROXIMATELY 0.1 FEET SOUTHERLY OF AN EAST/WEST BARBED WIRE FENCE. ACCEPTED SAID PIPE AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 26 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 2.0 FEET IN DIAMETER AND 4 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. BURIED THE FOUND 1 INCH IRON PIPE UPSIDE DOWN ALONGSIDE NEW MONUMENT. SET A U CHANNEL ALUMINUM POST WITH FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 1.0 FOOT SOUTHERLY. NO ORIGINAL BEARING TREES IN THE VICINITY. MADE NEW BEARING TREES, BASE BLAZE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT BASE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT1: AN 8 INCH THREE FORK JUNIPER, S72°E, 55.5 FEET TO MAG SPIKE AND WASHER AT CENTER RIGHT SIDE

BT2: AN 8 INCH FIVE FORK JUNIPER, N60°W, 68.0 FEET TO MAG SPIKE AND WASHER AT CENTER LEFT SIDE

MONUMENT DESCRIPTIONS:

300140




FOUND A 1 INCH IRON PIPE AND TAG STAMPED "RCE 27104" PER R2, ENCIRCLED BY A MOUND OF STONES 3 FEET IN DIAMETER AND 8 INCHES ABOVE THE GROUND. FOUND THE ORIGINAL 12x10x8 INCH STONE NEXT TO THE PIPE. ALSO FOUND A STEEL WITNESS POST 1.7 FEET NORTHWESTERLY OF THE MONUMENT. ACCEPTED SAID PIPE AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 24 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 2.5 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. BURIED THE FOUND 1 INCH PIPE AND STONE UPSIDE DOWN ALONGSIDE NEW MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 2.0 FEET NORTHERLY. MADE NEW BEARING TREES, BASE BLAZE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT BASE CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT1: A 6 INCH YELLOW PINE, S83°E, 62.1 FEET


BT2: A 12 INCH YELLOW PINE, S06°E, 105.4 FEET

300200




FOUND AN 18x12x18 INCH STONE LYING ALONGSIDE A 1 1/4 INCH IRON PIPE AND TAG STAMPED "RCE 27104" PER R2, 6 INCHES ABOVE THE GROUND. ALSO FOUND A STEEL WITNESS POST 2.3 FEET WESTERLY OF THE MONUMENT. ACCEPTED SAID PIPE AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 18 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 3.0 FEET IN DIAMETER AND 12 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. BURIED THE FOUND 1 1/4 INCH IRON PIPE AND STONE UPSIDE DOWN ALONGSIDE THE NEW MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 1.3 FEET NORTHERLY. NO ORIGINAL OR NEW BEARING TREES IN THE VICINITY.

300220




SET A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 24 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 2.0 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 1.0 FOOT SOUTHERLY. NO ORIGINAL OR NEW BEARING TREES IN THE VICINITY.

300240




FOUND A 28x14x12 INCH STONE MARKED "1/4" ON THE WESTERLY FACE, ENCIRCLED BY A MOUND OF STONES, 4 FEET IN DIAMETER AND 12 INCHES ABOVE THE GROUND, ACCEPTED SAID MARKED STONE AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 12 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 4.0 FEET IN DIAMETER AND 18 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. BURIED THE FOUND STONE UPSIDE DOWN ALONGSIDE NEW MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 1.5 FEET EASTERLY. NO ORIGINAL OR NEW BEARING TREES IN THE VICINITY.

300300



SEARCHED, FOUND NOTHING, ESTABLISHED BY DOUBLE PROPORTION FROM 300240 TO THE SOUTH, 300340 TO THE NORTH, 240300 TO THE WEST, AND 340300 TO THE EAST. SET A 3/4 INCH DIAMETER US FOREST SERVICE ALUMINUM CAP WITH MAGNET, STAMPED AS SHOWN, ON A 2 INCH DIAMETER IRON PIPE, 72 INCHES LONG, 64 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 3.0 FEET IN DIAMETER AND 8 INCHES ABOVE THE GROUND. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 2.0 FEET NORTHERLY. NO ORIGINAL OR NEW BEARING TREES IN THE VICINITY.

300340



FOUND A 10x10x24 INCH STONE MARKED "1/4" IN THE CENTER OF A STONE MOUND, ALSO FOUND A 2x2 HUB WITH A TACK ALONG SIDE SAID MARKED STONE. ACCEPTED MARKED STONE AS THE TRUE CORNER AND REPLACED WITH A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A 3/4 INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2 1/2 INCH DIAMETER POST, 30 INCHES LONG, 18 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 3.0 FEET IN DIAMETER AND 12 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. BURIED THE FOUND STONE UPSIDE DOWN ALONGSIDE THE NEW MONUMENT. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 2.0 FEET SOUTHERLY. NO ORIGINAL BEARING TREES IN THE VICINITY. MADE A NEW BEARING TREE, BASE BLAZE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT BASE CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT1: A 14 INCH JEFFREY PINE, N47°E, 60.7 FEET